

Retrieve , Create and Modify Investor level capital activity . Once created the transaction is in a pending state until booked in SEI's accounting systems which is not tracked via these APIs.

TAGS: insight, dealBoard, CRM,

ENDPOINT: Status

ENDPOINT DESCRIPTION:

Track the status of the pending transaction creation or modification.

PROD URL: <https://api.seic.com/v1/jobs/{appName}/status/{key}>

TEST URL: <https://test.api.seic.com/v1/jobs/{appName}/status/{key}>

TLS URL*: <https://mtls.api.seic.com/v1/jobs/{appName}/status/{key}>

*The TLS endpoint is only used if Server Based Application was selected during the App Registration process.

STEP 1

OAuth Token

STEP 2

Pass the OAuth Token and the App key to invoke this endpoint for a particular application

REQUEST PARAMETERS:

Name	Description	Data Type	Parameter Type
appName	This parameter identifies the application for which the job status API is being run. Valid value is "insight".	string	template
key	This value is returned by the POST API in the response as "jobStatusQueryKey".	string	template
Authorization	access_token value obtained from the Token endpoint.This is passed as "Bearer access_token"	string	header
AppKey	This is the Consumer Key provided during the App Registration process and is used to identify the user's application.	string	header

SAMPLE REQUEST:

```
curl -X GET \  
  https://api.seic.com/v1/jobs/insight/status/NjasfsdgTkkMDcvMjOTowMA== \  
  -H 'appkey: gsedgaerhDSHGRSH' \  
  -H 'authorization: Bearer ADsgdnnkjnfdIKJN' \  

```

REQUEST HEADER:

```
Authorization: Bearer ADsgdnnkjnfdIKJN  
AppKey: gsedgaerhDSHGRSH
```

RESPONSE PAYLOAD MODEL:

Name	Description	Data Type(L)
status	Defines the status for a specific pending transaction, such as 'Active' or 'Cancel'.	string(30)
batchId	SEI Accounting system generated identifier for batch representing a group of journal entries	string

RESPONSE ERRORS:

Name	Description
200	OK- The request has succeeded and the response has been returned.
400	Bad request - The server cannot or will not process the request due to an inaccurate request submitted by the client application. Please resubmit the request after making the required corrections indicated in the error response. For more Info on SEI Error Standards please refer to the API Standards FAQ under Support.
401	Unauthorized - Invalid authentication details have been provided. Also useful to trigger an authorization pop up if the API is used from a browser.
403	Forbidden-The SEI Server understood the request but refuses to fulfill it.
404	Not Found- The requested resource or the underlying resource does not exist. Please resubmit the request after making the required corrections
500	Internal Server Error - The SEI server was unable to fulfill the request due to an unknown condition. Please contact SEI for support. For More Info please refer to the "Response & Errors" FAQ under support.

SAMPLE RESPONSE:

```
{
  "status": "string",
  "batchId": "string",
  "message": "string",
  "validationMessage": [
    "string"
  ]
}
```

RESPONSE HEADER:

```
Content-Type: application/json
Status: 200 OK
requesttrackingid: 67e1ff68-164f-03ad-0f2d-5cbbfda56ec9
```